

ATOMIZING SPRAY (AS) NOZZLES

STANDARD SPRAY

■ PERFORMANCE DATA: FINE SPRAY

Inlet Conn. (in.)	Nozzle Type	Capacity Size	Dimensions			Flow Rate Capacity (gallons per minute)						
	NP7G		A(ft.)	B(ft.)	C(ft.)	20psi	40psi	60psi	80psi	100psi	125psi	150psi
3/4	●	1	3	5	3-1/4							
			5	6-1/2	4-1/4							
			8	7-1/2	4-3/4	.98	1.3	1.6	1.8	2.1	2.3	2.5
			11	8	5-1/4							
	●	1.5	3	8	5-1/2							
			5	9	6-1/2							
			8	10	7-1/2	1.5	2.0	2.4	2.8	3.1	3.4	3.7
			11	10-1/2	7-3/4							
	●	3	3	8-1/2	5-1/2							
			5	10	6-1/2							
			8	11	7	2.9	4.0	4.8	5.5	6.2	6.8	7.4
			11	11-1/2	7-1/2							
	●	5	3	9-1/2	6-1/4							
			5	11	7							
			8	12	7-3/4	4.8	6.7	8.1	9.2	10.3	11.3	12.4
			11	12-1/2	8							
1	●	6.5	3	10	9							
			5	11-1/2	9-1/4							
			8	13	10	6.2	9.1	10.5	11.9	13.3	14.5	16.1
			11	13-1/2	11-1/2							
	●	10	3	11	9-1/2							
			5	12-1/2	10							
			8	13-1/2	11	9.8	13.5	16.4	18.9	21	23	25
			11	14	12							
	●	12.5	3	12	10							
			5	13-1/4	11							
			8	14	12	12.0	17.0	20	23	25	28	30
			11	14-1/2	12-1/2							
	●	16	3	12-1/2	10-1/2							
			5	13-3/4	12							
			8	14-1/2	13	15.4	22	26	30	33	37	40
			11	15	13-1/4							

■ DIMENSIONS AND WEIGHTS

Nozzle	Nozzle Type	Inlet Conn. (in.)	L (in.)	D (Dia.) (in.)	Net Weight (oz.)
		3/4	1.820	2.125	10.0
	NP7G (F)	1	3.313	4.063	43.3

Based on the largest/heaviest version of each type.

■ ORDERING INFO

Unit Formula Complete Nozzle				
NP7G	-	1.5	-	3/4
Nozzle		Capacity		Inlet
Type				Connection
				SS
				Material

Available materials: Brass (leave blank), 303/304 Stainless (SS), 316L Stainless (316)

