


HOLLOW CONE SPRAY NOZZLES

■ PERFORMANCE DATA: WIDE ANGLE SPRAY

Inlet Conn. (in.)	Nozzle Type	Capacity Size	Flow Rate Capacity (gallons per minute)						
	NPAF		5psi	10psi	20psi	40psi	60psi	80psi	
1/8	•	.37	.27	.38	.53	.75	.92	1.1	1.2
	•	.5	.35	.50	.70	1.0	1.2	1.4	1.6
	•	.75	.53	.75	1.1	1.5	1.8	2.1	2.4
1/4	•	1	.71	1.0	1.4	2.0	2.5	2.8	3.2
	•	1.5	1.1	1.5	2.1	3.0	3.7	4.2	4.7
	•	2	1.4	2.0	2.8	4.0	4.9	5.6	6.3
	•	2.5	1.8	2.5	3.5	5.0	6.1	7.1	7.9
3/8	•	3	2.1	3.0	4.2	6.0	7.3	8.5	9.5
	•	3.5	2.5	3.5	5.0	7.0	8.6	9.9	11.0
	•	4	2.8	4.0	5.7	8.0	9.8	11.3	12.6
	•	4.5	3.2	4.5	6.4	9.0	11.0	12.7	14.2
	•	5	3.5	5.0	7.1	10.0	12.3	14.2	15.8

Spray angles available in 120, 150, and 180 degrees

Standard	Nozzle Type	Inlet Conn. (in.)	HEX (in)	C (in)	Net Weight (oz)
	NPAF (M)	1/8	1/2	1.19	.8
		1/4	5/8	1.31	1
		3/8	7/8	1.75	2.9

■ ORDERING INFO

Unit Formula Complete Nozzle							
NPAF.	-	.5	-	150	-	1/8	- 316
Nozzle	Capacity			Spray	Inlet		Material
Type				Angle	Connection		

Available materials: Brass (leave blank), 303/304 Stainless (SS), 316L Stainless (316)