




HOLLOW CONE NOZZLES

STANDARD SPRAY

MATERIALS

Material	Material Code	Nozzle Type					
		NPA	NPAX	NPB	NPBX	FC	FCX
Bar Stock:							
Brass	(none)	•	•	•	•		
Mild Steel	1	•	•	•	•		
303 Stainless Steel	SS	•	•	•	•		
316 Stainless Steel	316SS	•	•	•	•		
Polypropylene	PP						
Polyvinyl Chloride	PVC	•		•			
Cast:							
Mild Steel	1					•	•
Brass	(none)					•	•
303 stainless Steel	SS						
316 Stainless Steel	316SS					•	•

DIMENSIONS AND WEIGHTS

Standard	Nozzle Type	Inlet Conn. (in.)	A (mm)	B (mm)	C (mm)	D (mm)	L (mm)	Net Weight (kg)
	NPA, NPAX (F)	1/8	17.5	16	12	20	25.5	.04
		1/4	22.5	19	13.5	23	32	.08
		3/8	26.5	22.5	17.5	28.5	37.5	.12
		1/2	35	28.5	21.5	36	49.5	.25
		3/4	40	32	24	40	55.5	.31
	NPB, NPBX (M)	1/8	22.5	16	12	20	30.5	.04
		1/4	25.5	19	13.5	23	35	.07
		3/8	28.5	22.5	17.5	28.5	40	.11
		1/2	35	28.5	21.5	36	49.5	.20
		3/4	41.5	32	24	40	57.5	.31
	FC (F)	1/2	33.5	33.5	5.5	18.5	48	.13
		3/4	38	42	7.5	23	58	.20
	FCX (F)	1	44.5	47	9	26	66.5	.31
		1-1/4	50.9	55.6	11.1	31.7	77.8	.57
		1-1/2	61.9	73	14.3	42.1	93.6	.79
		2	74.6	93.6	18.2	53.1	115.1	1.4
		2-1/2	88.9	114.3	23.8	68.3	140.5	1.9

Based on largest/heaviest version of each type.