


FLAT SPRAY NOZZLES

STANDARD SPRAY

DIMENSIONS AND WEIGHTS

Standard	Nozzle Type	Inlet Conn. (in.)	Length (mm)	Hex. (mm)	Net Weight (kg)
	NPHV (M)	1/8	22	12.7	.02
		1/4	23	14.3	.03
	NPHVL (M)	1/8	36	12.7	.02
		1/4	38	14.3	.03

	NPHU (M)	1/8	22	12.7	.02
		1/4	25	14.3	.03
		3/8	32	17.5	.04
		1/2	38	22.2	.06
		3/4	51	27	.14



MATERIALS

Material	Material Code	Nozzle Type				
		NPHV	NPHVL		NPHU	
Brass	(none)	•	•		•	
Mild Steel	1	•			•	
303 Stainless Steel	SS	•	•		•	
316 Stainless Steel	316SS	•	•		•	
Polyvinyl Chloride	PVC				•	

Other materials available upon request.

Mesh Selection Guide	
Orifice Dia. in. (mm)	Recommended Screen Mesh
Up through .018 (.46)	200
.019 (.47) through .031 (.79)	100
.032 (.80) and larger	50

ORDERING INFO

Standard Spray Nozzle						
NPH	1/4	V	-	SS	110	01
Nozzle Prefix	Inlet Conn.	Nozzle Type	Material Code	Spray Angle	Capacity Size	

BSPT connections require the addition of a "B" prior to the inlet connection.