

# WIDE ANGLE FLAT SPRAY NOZZLES

## WIDE ANGLE SPRAY



### 【 NPK 】




1/8" to 1/4" NPT or BSPT (M)

### ■ FEATURES AND BENEFITS

- Wide-angle flat fan spray pattern with uniform distribution and medium impact.
- Smooth fluid flow passage to minimize clogging occurs.
- Fluid flow channel provides a very uniform spray effect.
- Precision engineered for dependable, accurate control of deflection and spray angle.

### ■ DIMENSIONS AND WEIGHTS

Standard	Nozzle Type	Inlet Conn. (in.)	Length (mm)	Hex. (mm)	Net Weight (kg)
	NPK (M)	1/8	22	12.7	.02
		1/4	23	14.3	.03
		3/8	44.5	17.5	.06
		1/2	51	22.2	.11
		3/4	65.1	38.1	.40
		1	92.1	47.6	.91

### ■ MATERIALS

Material	Material Code	Nozzle Type
		NPK
Brass	(none)	•
303 Stainless Steel	SS	•
316 Stainless Steel	316SS	•
Polyvinyl Chloride	PVC	•

Other materials available upon request.

### ■ ORDERING INFO

Standard Spray Nozzle				
1/8	NPK	-	SS	3
1	1	1	1	1
Inlet Conn.	Nozzle Type	Material Code	Capacity Size	

BSPT connections require the addition of a "B" prior to the inlet connection.

### ■ TYPICAL APPLICATION

- Cooling
- Film washing
- Fire suppression / Prevention
- Degassing
- Washing and filling machine cleaning
- Jet mixing
- Water curtain