

QUICK CONNECT FLAT SPRAY NOZZLES

STANDARD SPRAY



■ PERFORMANCE DATA: STANDARD ANGLE SPRAY

Nozzle Type	Spray Angle at 3 bar				Capacity Size	Flow Rate Capacity (liters per minute)										
NPQCMEG	0° * (Red)	15° (Yellow)	25° (Green)	40° (White)		20 bar	35 bar	50 bar	80 bar	100 bar	140 bar	170 bar	200 bar	250 bar	275 bar	
●			●	●	02	2.0	2.7	3.2	4.1	4.6	5.4	5.9	6.4	7.2	7.6	
●	●	●	●	●	03	3.1	4.0	4.8	6.1	6.8	8.1	8.9	9.7	10.8	11.3	
●	●	●	●	●	035	3.6	4.7	5.6	7.1	8.0	9.4	10.4	11.3	12.6	13.2	
●	●	●	●	●	04	4.1	5.4	6.4	8.2	91	10.8	11.9	129	14.4	15.1	
●	●	●	●	●	045	4.6	6.1	7.3	9.2	10.3	121	13.4	14.5	16.2	17	
●	●	●	●	●	05	5.1	6.7	8.1	10.2	11.4	13.5	14.9	16.1	18	18.9	
●	●	●	●	●	055	5.6	7.4	8.9	112	12.5	14.8	16.3	17.7	19.8	21	
●	●	●	●	●	06	6.1	8.1	9.7	122	13.7	16.2	17.8	19.3	22	23	
●	●	●	●	●	065	6.6	8.8	10.5	13.3	14.8	17.5	19.3	21	23	25	
●	●	●	●	●	07	7.1	9.4	11.3	14.3	16	18.9	21	23	25	26	
●	●	●	●	●	075	7.6	10.1	12.1	153	17.1	20	22	24	27	28	
●	●	●	●	●	08	8.2	10.8	12.9	16.3	18.2	22	24	26	29	30	
●	●	●	●	●	09	9.2	12.1	14.5	18.3	21	24	27	29	32	34	
●	●	●	●	●	10	10.2	13.5	16.1	20	23	27	30	32	36	38	
●	●	●	●	●	12	12.2	16.2	19.3	24	27	32	36	39	43	45	
●		●		●	15	15.3	20	24	31	34	40	45	48	54	57	

*0° =Solid Stream.