


QUICK CONNECT SOLID CONE SPRAY NOZZLES STANDARD SPRAY

DIMENSIONS AND WEIGHTS

Standard	Nozzle Type	Length (mm)	Dia. (mm)	Net Weight (kg)
	NPQJ +NPQG	61	25.4	.14
	NPQJJ +NPQG	59	22.2	.13
	NPQJL +NPQLG	70.5	28.6	.23
	NPQJL +NPQLG	72	28.6	.21
	NPQJ +NPQH	50	25.4	.07
	NPQJJ +NPQH	47	25.4	.06
	NPQJL +NPQLH	57	28.6	.13
	NPQJL +NPQLH	58	28.6	.13

BODY TYPES

Inlet Conn. (in.)	Standard Body			
	Conn. F		Conn. M	
	NPQJ	NPQJL	NPQJJ	NPQJL
1/8	•		•	
1/4	•		•	
3/8	•	•	•	•
1/2	•	•	•	•

MATERIALS

Material	Material Code	Spray Tip			
		NPQG	NPQLG	NPQH	NPQLH
Brass	(none)	•	•	•	•
303 Stainless Steel	SS	•	•	•	•

Standard quick connect full nozzles available in either brass with a Buna-N seal or stainless steel with a Viton® seal.

ORDERING INFO

Quick Connect Full Cone Complete Nozzle					
Nozzle Body			Spray Tip		
1/4	NPQJ	- SS	+	NPQH	- SS
Inlet Conn.	Body Type	Material Code		Tip Type	Material Code
					Capacity Size