

QUICK CONNECT FLAT SPRAY NOZZLES

STANDARD SPRAY

DIMENSIONS AND WEIGHTS

Standard	Nozzle Type	Length (mm)	Hex. (mm)	Width (mm)	Net Weight (kg)
	NPQJJS + NPQSV 28	14.3	-	-	.03
	NPQJJS + NPQSU 30	14.3	-	-	.03
	NPQJ + NPQV 55	25.4	-	-	.07
	NPQJJ + NPQV 53	25.4	-	-	.06
	NPQJ + NPQU 51	25.4	-	-	.08
	NPQJJ + NPQU 49	25.4	-	-	.06
	NPQJL + NPQU 59	28.6	-	-	.13
	NPQJL + NPQU 60	28.6	-	-	.12

BODY TYPES

Inlet Conn. (in.)	Standard Body				
	Conn. F		Conn. M		
	NPQJ	NPQJL	NPQJJS	NPQJJ	NPQJL
1/8	•		•	•	
1/4	•		•	•	
3/8	•	•		•	•
1/2	•	•		•	•

ORDERING INFO

Quick Connect Flat Complete Nozzle							
Nozzle Body				Spray Tip			
1/4	NPQJJ	SS	+	NPQV	SS	95	05
Inlet Conn.	Body Type	Material Code		Tip Type	Material Code	Spray Angle	Capacity Size

Add "A" to the capacity size for external O-ring. Example: 02A
 BSPT connections require the addition of a "B" prior to the nozzle body inlet connection

MATERIALS

Material	Material Code	Spray Tip				
		NPQSV	NPQSU	NPQV	NPQU	NPQU
Brass	(none)	•	•	•	•	•
303 Stainless Steel	SS	•	•	•	•	•

Standard Quick Flat nozzles available in either brass with a Buna-N seal or stainless steel with a Viton® seal.